

Wheel Features

Tread Material:	PU	Core Material:	High Strength PP
Bearing:	Ball Bearing	Tread Hardness:	95A±3
Temperature:	-20°C~50°C	Running Speed:	3.2km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.

- ✔ High quality polyurethane is resistant to oil and wear.
- ✔ 2 precision ball bearings, flexible rotation
- ✔ Moderate hardness, can effectively protect the ground.
- ⚠ Hot and humid conditions shorten service life.





Rolling resistance	■ ■ ■ ■ □	Very good
Wear resistance	■ ■ ■ ■ ■	Excellent
Operating noise	■ ■ ■ ■ □	Very good
Floor surface preservation	■ ■ ■ ■ □	Very good

Bracket Features

- ✔ Easy to operate, convenient to release the brake
- ✔ Bracket made of pressed steel plate, firm and strong
- ✔ Two sets of balls riveted structure has small clearance and high strength.
- ✔ Thickened top plate, resistant to compress which is hard to deform
- ✔ Blue galvanized, ROHS/REACH passed, salt spray test over 72 hours

Parameter (mm)	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
1.5"	40 kg	40	28	63	26	46	78
2"	60 kg	50	28	74	24	49	78



Mounting Drawing




Plate Swivel/Brake





Plate Fixed



Threaded Stem

Product ID					
Product Images					
Wheel Size	Plate swivel	Plate fixed	Plate swivel brake	Threaded stem	Threaded stem brake
1.5"	18A01-1715	18A03-1715	18A02-1715	18A04-1715	18A05-1715
2"	18A06-1716	18A08-1716	18A07-1716	18A09-1716	18A10-1716

Product Details

Double steel bowl design, stable structure, flexible rotation.



Zinc-plated, blue surface treatment bracket, the salt spray for 72 hours. ARC shape, Nice appearance and high strength.



The brake is simple and can be operated by single finger.



Double ball bearing, flexible rotation and excellent performance of loading capacity.

