

Wheel Features

Tread Material:	High Strength PP	Core Material:	High Strength PP
Bearing:	Ball Bearing	Tread Hardness:	75D±3
Temperature:	-25°C~80°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ 2 precision ball bearings,flexible rotation
- ✔ Injection polypropylene,integral injection,low starting force,economical choice
- ✔ No deformation,anti-aging,endurable to humid environment
- ⚠ Hard wheel material,it may damage epoxy flooring
- ⚠ Wheel running may cause some noise






Rolling resistance	■ ■ ■ ■ ■	Excellent
Wear resistance	■ ■ ■ □ □	Good
Operating noise	■ □ □ □ □	Acceptable
Floor surface preservation	■ □ □ □ □	Acceptable

Bracket Features

- ✔ ON/OFF pedals,stable braking effect,easy to operate
- ✔ Bracket made of pressed steel plate,firm and strong
- ✔ Thickened top plate,resistant to compress which is hard to deform
- ✔ Reinforced riveted,close gap,high structural strength
- ✔ Dustproof ring effectively protects grease for long sevice life
- ✔ Environmentally friendly colour galvanized,salt spray test over 72 hours

Parameter (mm)							
Wheel Size	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
3"	105 kg	75	30	108	34	71.5	116.5
3.5"	115 kg	88	32	120	32	76	116
4"	135 kg	100	32	135	32	82	116
5"	145 kg	125	32	160	32	94.5	121



Mounting Drawing




Plate Swivel







Plate Fixed



Threaded Stem

Product ID	Product Images	Wheel Size	Plate swivel	Plate fixed	Plate swivel brake	Threaded stem	Threaded stem brake
3"		20A01-1040	20AB1-1040	20A3B-1040	20A04-1040	20A7B-1040	
3.5"		20A10-1041	20AB2-1041	20A4B-1041	20A13-1041	20A8B-1041	
4"		20A19-1042	20AB3-1042	20A5B-1042	20A22-1042	20A9B-1042	
5"		20A28-1043	20AB4-1043	20A6B-1043	20A31-1043	20A1B-1043	

Product Details

ON/OFF brake is easy to operate.



Fancy riveting has tight clearance, the structure is stable. Dust ring can effectively protect dust and grease lubrication.



The surface treatment of bracket is Zinc plated, blue, which can meet the salt spray test for 72 hours.



Reinforced wheel ribs with high strength. Bearing cover is tight clearance.

