

Wheel Features

Tread Material:	Supper PU	Core Material:	High Strength PP
Bearing:	Ball Bearing	Tread Hardness:	95A±3
Temperature:	-20°C~50°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ 2 precision ball bearings,flexible rotation
- ✔ Injection polyurethane,glue-free self lock structureoil resistance,wear resistance
- ✔ Environmental protection,quiet,effectively protect the floor
- ✔ With metal covers,thread-proof design
- ⚠ High temperature and humidity may shortened service life






Rolling resistance	■ ■ ■ ■ □	Very good
Wear resistance	■ ■ ■ ■ ■	Excellent
Operating noise	■ ■ ■ ■ □	Very good
Floor surface preservation	■ ■ ■ ■ □	Very good

Bracket Features

- ✔ ON/OFF pedals,stable braking effect,easy to operate
- ✔ Bracket made of pressed steel plate,firm and strong
- ✔ Thickened top plate,resistant to compress which is hard to deform
- ✔ Reinforced riveted,close gap,high structural strength
- ✔ Dustproof ring effectively protects grease for long sevice life
- ✔ Blue galvanized,ROHS/REACH passed,salt spray test over 72 hours

Parameter (mm)							
Wheel Size	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
3"	110 kg	75	32	108	34	71.5	116.5
4"	140 kg	100	32	135	32	82	116
5"	150 kg	125	32	160	32	94.5	121



Mounting Drawing




Plate Swivel





Plate Fixed



Threaded Stem

Product ID					
Product Images					
Wheel Size	Plate swivel	Plate fixed	Plate swivel brake	Threaded stem	Threaded stem brake
3"	20A01-0370	20AB1-0370	20A3B-0370	20A04-0370	20A7B-0370
4"	20A19-0371	20AB3-0371	20A5B-0371	20A22-0371	20A9B-0371
5"	20A28-0372	20AB4-0372	20A6B-0372	20A31-0372	20A1B-0372

Product Details




ON/OFF brake is easy to operate.



Fancy riveting has tight clearance, the structure is stable. Dust ring can effectively protect dust and grease lubrication.

The surface treatment of bracket is Zinc plated, blue, which can meet the salt spray test for 72 hours.



Double ball precision bearings is flexible rotation.

