

Wheel Features

Tread Material:	Supper PU	Core Material:	High Strength PP
Bearing:	Single Ball Bearing	Tread Hardness:	95A±3
Temperature:	-20°C~50°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ Precision ball bearing,flexible rotation
- ✔ Injection polyurethane,glue-free self lock structureoil resistance,wear resistance
- ✔ Environmental protection,quiet,effectively protect the floor
- ✔ With plastic covers,thread-proof design
- ⚠ High temperature and humidity may shortened service life






Rolling resistance	■ ■ ■ ■ □	Very good
Wear resistance	■ ■ ■ ■ ■	Excellent
Operating noise	■ ■ ■ ■ □	Very good
Floor surface preservation	■ ■ ■ ■ □	Very good

Bracket Features

- ✔ ON/OFF pedals,stable braking effect,easy to operate
- ✔ Bracket made of pressed steel plate,firm and strong
- ✔ Thickened top plate,resistant to compress which is hard to deform
- ✔ Reinforced riveted,close gap,high structural strength
- ✔ Dustproof ring effectively protects grease for long sevice life
- ✔ Blue galvanized,ROHS/REACH passed,salt spray test over 72 hours

Parameter (mm)							
Wheel Size	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
3"	100 kg	75	32	108	34	71.5	116.5
4"	130 kg	100	32	135	32	82	116
5"	140 kg	125	32	160	32	94.5	121



Mounting Drawing




Plate Swivel





Plate Fixed




Threaded Stem

Product ID					
Wheel Size	Plate swivel	Plate fixed	Plate swivel brake	Threaded stem	Threaded stem brake
3"	20A01-1354	20AB1-1354	20A3B-1354	20A04-1354	20A7B-1354
4"	20A19-1355	20AB3-1355	20A5B-1355	20A22-1355	20A9B-1355
5"	20A28-1356	20AB4-1356	20A6B-1356	20A31-1356	20A1B-1356

Product Details

ON/OFF brake is easy to operate.



Fancy riveting has tight clearance, the structure is stable. Dust ring can effectively protect dust and grease lubrication.



The surface treatment of bracket is Zinc plated, blue, which can meet the salt spray test for 72 hours.



Concave-convex designed cover, three-dimensional and beautiful. The arc wheel is easy to move.

