

Wheel Features

Tread Material:	Rubber	Core Material:	Nylon
Bearing:	Single Ball Bearing	Tread Hardness:	75A±3
Temperature:	-20°C~50°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ Precision ball bearing, flexible rotation
- ✔ Natural rubber material, injection bonding molding, high rebound
- ✔ Environmental protection, quiet, effectively protect the floor
- ⚠ High temperature and humidity may shortened service life






Rolling resistance	■ ■ ■ ■ □	Very good
Wear resistance	■ ■ ■ ■ □	Very good
Operating noise	■ ■ ■ ■ ■	Excellent
Floor surface preservation	■ ■ ■ ■ ■	Excellent

Bracket Features

- ✔ ON/OFF pedals, stable braking effect, easy to operate
- ✔ Bracket made of pressed steel plate, firm and strong
- ✔ Thickened top plate, resistant to compress which is hard to deform
- ✔ Reinforced riveted, close gap, high structural strength
- ✔ Dustproof ring effectively protects grease for long service life
- ✔ Blue galvanized, ROHS/REACH passed, salt spray test over 72 hours

Parameter (mm)	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
3"	80 kg	75	32	108	34	71.5	116.5
4"	90 kg	100	32	135	32	82	116
5"	120 kg	125	32	160	32	94.5	121



Mounting Drawing




Plate Swivel





Plate Fixed



Threaded Stem

Product ID					
Product Images					
Wheel Size	Plate swivel	Plate fixed	Plate swivel brake	Threaded stem	Threaded stem brake
3"	20A01-1044	20AB1-1044	20A3B-1044	20A04-1044	20A7B-1044
4"	20A19-1045	20AB3-1045	20A5B-1045	20A22-1045	20A9B-1045
5"	20A28-1046	20AB4-1046	20A6B-1046	20A31-1046	20A1B-1046

Product Details

ON/OFF brake is easy to operate.



Fancy riveting has tight clearance, the structure is stable. Dust ring can effectively protect dust and grease lubrication.



The surface treatment of bracket is Zinc plated, blue, which can meet the salt spray test for 72 hours.



Concave-convex designed cover, three-dimensional and beautiful, anti-winding. The soft natural rubber wheel has high rebound properties to protect the floor.

