

Wheel Features

Tread Material:	TPR	Core Material:	High Strength PP
Bearing:	Single Ball Bearing	Tread Hardness:	75A±3
Temperature:	-15°C~60°C	Running Speed:	3.2km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ Precision ball bearing,flexible rotation
- ✔ Advanced thermo-plastic rubber,silent running,elastic to protect floor
- ✔ Environmental protection,quiet,effectively protect the floor
- ✔ With plastic covers,thread-proof design
- ⚠ Economical material with common load capacity






Rolling resistance	■ ■ ■ □ □	Good
Wear resistance	■ ■ ■ □ □	Good
Operating noise	■ ■ ■ ■ ■	Excellent
Floor surface preservation	■ ■ ■ ■ ■	Excellent

Bracket Features

- ✔ ON/OFF pedals,stable braking effect,easy to operate
- ✔ Bracket made of pressed steel plate,firm and strong
- ✔ Thickened top plate,resistant to compress which is hard to deform
- ✔ Reinforced riveted,close gap,high structural strength
- ✔ Dustproof ring effectively protects grease for long sevice life
- ✔ Blue galvanized,ROHS/REACH passed,salt spray test over 72 hours

Parameter (mm)							
Wheel Size	Capacity	Wheel Dia.	Wheel width	Total height	Offset	Swivel Radius	Swivel Radius
3"	70 kg	75	32	108	34	71.5	116.5
4"	80 kg	100	32	135	32	82	116
5"	90 kg	125	32	160	32	94.5	121



Mounting Drawing




Plate Swivel





Plate Fixed



Threaded Stem

Product ID					
Wheel Size	Plate swivel	Plate fixed	Plate swivel brake	Threaded stem	Threaded stem brake
3"	20A01-1593	20AB1-1593	20A3B-1593	20A04-1593	20A7B-1593
4"	20A19-1594	20AB3-1594	20A5B-1594	20A22-1594	20A9B-1594
5"	20A28-1595	20AB4-1595	20A6B-1595	20A31-1595	20A1B-1595

Product Details

ON/OFF brake is easy to operate.



Fancy riveting has tight clearance, the structure is stable. Dust ring can effectively protect dust and grease lubrication.



The surface treatment of bracket is Zinc plated, blue, which can meet the salt spray test for 72 hours.



Concave-convex designed cover, three-dimensional and beautiful, anti-winding. Soft TPR wheel is mute and can protect the floor effectively.



[English]

