

# 35A 系列 SERIES Cast Iron (Black)



## Wheel Features

Tread Material:	Cast Iron	Core Material:	Cast Iron
Bearing:	Ball Bearing	Tread Hardness:	> 100D
Temperature:	-30°C~300°C	Running Speed:	4km/h



Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.

- ✔ 2 precision ball bearings, flexible rotation
- ✔ Casting iron wheel, high load capacity, high temperature resistance, lowest starting force
- ✔ Painted, anti-rust and anti-corrosion
- ⚠ Hard wheel material, it may cause indentations on floor
- ⚠ Easy to rust, avoid using in wet environment
- ⚠ Wheel running may cause some noise





Rolling resistance	■ ■ ■ ■ □	Very good
Wear resistance	■ ■ ■ ■ □	Very good
Operating noise	■ □ □ □ □	Acceptable
Floor surface preservation	■ □ □ □ □	Poor



## Bracket Features

- ✔ Steel plate pressed and fully welded, firm and strong
- ✔ Top plate and ball tracks are quenched to enhance strength and prolong service life
- ✔ Reinforced riveted, close gap, high structural strength
- ✔ Blue galvanized, ROHS/REACH passed, salt spray test over 72 hours
- ✔ ON/OFF pedals, stable braking effect, easy to operate
- ✔ Brake part is replaceable, convenient to maintain

Parameter (mm)							
Wheel Size	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
5"	380 kg	125	48	165	38	101	151
6"	450 kg	150	50	190	44	119	154
8"	460 kg	200	50	240	54	154	173



Mounting Drawing



Product ID					
Product Images					
Wheel Size	Plate swivel	Plate fixed	Plate swivel brake	Threaded stem	Threaded stem brake
5"	35A63-1125	35A65-1125	35A64-1125	35A97-1125	35A94-1125
6"	35A66-1126	35A68-1126	35A67-1126	35A93-1126	35A98-1126
8"	35A69-1127	35A71-1127	35A70-1127	35A99-1127	35AA1-1127

Product Details




ON/OFF brake is easy to operate. Brake components can be replaced with screw connecting.



Grease nipple is convenient for maintenance. Fancy riveted structure with gap tightly.

Quenched Ball Track has slight abrasion.

Non-quenched Ball Track' s abrasion and gap clearly.



Comparison after 10000times Rotational test.



The wheel is thick and durable, painted wheel core with anti-rust treatment.

