## Antiskid PU on Plastic Core (Black)



## Wheel Features

SERIES


35A

Tread Material:	PU	Core Material:	РР
Bearing:	Ball Bearing	Tread Hardness:	95A±3
Temperature:	-20°C~50°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.

- 2 precision ball bearings,flexible rotation
- 🎸 Injection polyurethane,glue-free self lock structureoil resistance,wear resistance
- Environmental protection, quiet, effectively protect the floor
- 10 Not water-proof, humid environment may accelerate aging of the wheel
- Biodegradable material, recommended to use within 1 year of prodution for best performance







Bracket Features

- 💎 Steel plate pressed and fully welded,firm and strong
- 🤣 Top plate and ball tracks are quenched to enhance strength and prolong service life
- Reinforced riveted,close gap,high structural strength
- Servironmentally friendly colour galvanized,salt spray test over 48 hours
- ON/OFF pedals, stable braking effect, easy to operate
- 🤣 Brake part is replaceable,convenient to maintain

Parameter	57	$\frown$	П		-	r	R
(mm)	KG	$(\circ)$			$\langle \rangle$	(P	E.
Wheel Size	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
5"	280 kg	125	50	165	38	101	151
6"	320 kg	150	50	190	44	119	154
8"	350 kg	200	50	240	54	154	173






[English]



Antiskid PU on Plastic Core (Black)



Mounting Drawing



Product ID			T	
Product Images	C			
Wheel Size	Plate swivel	Plate fixed	Plate swivel brake	
5"	35A72-1121	35A74-1121	35A73-1121	
6"	35A75-1122	35A77-1122	35A76-1122	
8"	35A78-1123	35A80-1123	35A79-1123	

Product Details

ON/OFF brake is easy to operate. Brake components can be replaced with screw connecting.




Grease nipple is convenient for maintenance. Dust ring can protect the grease and dustproof effectively.

Quenched Ball Track has slight abrasion.

Non-quenched Ball Track' s abrasion and gap clearly.



Pattern wheel surface, effectively anti-slip, plastic cover, Lightweight and anti-winding.



Comparison after 10000times Rotational test.

