

Wheel Features

Tread Material:	TPR	Core Material:	High Strength PP
Bearing:	Ball Bearing	Tread Hardness:	70A±3
Temperature:	-15°C~60°C	Running Speed:	3.2km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ 2 precision ball bearings,flexible rotation
- ✔ Advanced thermo-plastic rubber,silent running,elastic to protect floor
- ✔ Environmental protection,quiet,effectively protect the floor
- ⚠ Economical material with common load capacity





Rolling resistance	■ ■ ■ □ □	Good
Wear resistance	■ ■ ■ □ □	Good
Operating noise	■ ■ ■ ■ ■	Excellent
Floor surface preservation	■ ■ ■ ■ ■	Excellent



Bracket Features

- ✔ Steel plate pressed and fully welded,firm and strong
- ✔ Top plate and ball tracks are quenched to enhance strength and prolong service life
- ✔ Reinforced riveted,close gap,high structural strength
- ✔ Blue galvanized,ROHS/REACH passed,salt spray test over 72 hours
- ✔ ON/OFF pedals,stable braking effect,easy to operate
- ✔ Brake part is replaceable,convenient to maintain

Parameter (mm)	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
4"	140 kg	100	50	145	34	84	148
5"	180 kg	125	50	165	38	101	151
6"	230 kg	150	50	190	44	119	154
8"	280 kg	200	50	240	54	154	173



Mounting Drawing



Product ID	Product Images	Wheel Size	Plate swivel	Plate fixed	Plate swivel brake	Threaded stem	Threaded stem brake
4"		35A60-1531	35A62-1531	35A61-1531	35A95-1531	35A96-1531	
5"		35A63-1532	35A65-1532	35A64-1532	35A97-1532	35A94-1532	
6"		35A66-1533	35A68-1533	35A67-1533	35A93-1533	35A98-1533	
8"		35A69-1534	35A71-1534	35A70-1534	35A99-1534	35AA1-1534	

Product Details

ON/OFF brake is easy to operate. Brake components can be replaced with screw connecting.




Grease nipple is convenient for maintenance. Fancy riveted structure with gap tightly.



Quenched Ball Track has slight abrasion.

Non-quenched Ball Track' s abrasion and gap clearly.



Comparison after 10000times Rotational test.

Thermoplastic elastomer, very soft, can protect the floor effectively and no trace after working.

