

Wheel Features

Tread Material:	Cast Iron	Core Material:	Cast Iron
Bearing:	Ball Bearing	Tread Hardness:	> 100D
Temperature:	-30°C~300°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ 2 precision ball bearings,flexible rotation
- ✔ Casting iron wheel,high load capacity,high temperature resistance,lowest starting force
- ⚠ Easy to rust,avoid using in wet environment
- ⚠ Wheel running may cause some noise






Rolling resistance	■ ■ ■ ■ □	Very good
Wear resistance	■ ■ ■ ■ □	Very good
Operating noise	■ ■ □ □ □	Acceptable
Floor surface preservation	■ ■ □ □ □	Acceptable


Bracket Features

- ✔ Single-piece forged base,fully welded,impact resistance and high load capacity
- ✔ Plane bearing,high load capacity,impact resistance and flexible steering
- ✔ Radial conical bearing,high load capacity and impact resistance
- ✔ Powder spray treatment,superior anti-rust and anti-corrosion performance,salt spray test over 72 hours
- ✔ ON/OFF pedals,stable braking effect,easy to operate
- ✔ Brake part is replaceable,convenient to maintain

Parameter (mm)	Capacity (KG)	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius (r)	Swivel Radius (R)
5"	600 kg	125	50	175	34	97	151
6"	700 kg	150	50	200	38	113	151
8"	800 kg	200	50	248	47	147	175



Mounting Drawing



Product ID			
Product Images			
Wheel Size	Plate swivel	Plate fixed	Plate swivel brake
5"	35B01-1125	35B03-1125	35B02-1125
6"	35B04-1126	35B06-1126	35B05-1126
8"	35B07-1127	35B09-1127	35B08-1127

Product Details

ON/OFF brake is easy to operate. Brake components can be replaced with screw connecting.



Planar pressure bearings and radial conical bearings, with high load, impact resistance, flexible steering.



Double-sided welding, with 10mm thickened bottom plate and 8mm thickened wings.



The material is thick and durable. The wheel core is painted with anti-rust treatment.



[English]

