

Wheel Features

Tread Material:	TPR	Core Material:	High Strength PP
Bearing:	Ball Bearing	Tread Hardness:	80A±3
Temperature:	-15°C~60°C	Running Speed:	3.2km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.










- ✔ 2 precision ball bearings,flexible rotation
- ✔ Advanced thermo-plastic rubber,silent running,elastic to protect floor
- ✔ Environmental protection,quiet,effectively protect the floor
- ⚠ Economical material with common load capacity





Rolling resistance	■ ■ ■ □ □	Good
Wear resistance	■ ■ ■ □ □	Good
Operating noise	■ ■ ■ ■ ■	Excellent
Floor surface preservation	■ ■ ■ ■ ■	Excellent


Bracket Features







- ✔ Steel plate pressed and welded,firm and strong
- ✔ Reinforced riveted,close gap,high structural strength
- ✔ Blue galvanized,ROHS/REACH passed,salt spray test over 72 hours
- ✔ Easy to operate,convenient to release the brake
- ✔ Dustproof ring effectively protects grease for long sevice life

Parameter (mm)							
Wheel Size	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
4"	140 kg	100	50	145	34	84	148
5"	180 kg	125	50	165	38	101	151
6"	230 kg	150	50	190	44	119	154
8"	280 kg	200	50	240	54	154	173



Mounting Drawing



Product ID						
Product Images						
Wheel Size	Plate swivel	Plate fixed	Plate swivel brake	Plate swivel brake	Plate swivel brake	Plate swivel brake
4"	35C01-1706	35C04-1706	35C20-1706	35C65-1706	35C03-1706	35C56-1706
5"	35C05-1707	35C08-1707	35C21-1707	35C66-1707	35C07-1707	35C57-1707
6"	35C09-1708	35C12-1708	35C22-1708	35C67-1708	35C11-1708	35C58-1708
8"	35C13-1709	35C16-1709	35C23-1709	35C68-1709	35C15-1709	35C59-1709

Product Details

Fancy riveting has tight clearance, the structure is stable and high strength.



Dust ring can effectively protect dust and grease lubrication.



The surface treatment of bracket is Zinc plated, blue, which can meet the salt spray test for 72 hours. The bracket is curved shape, nice appearance and high strength.

