

Wheel Features

Tread Material:	PU	Core Material:	Cast Iron
Bearing:	Ball Bearing	Tread Hardness:	95A±3
Temperature:	-25°C~60°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ 2 precision ball bearings,flexible rotation
- ✔ Polyurethane on casting iron core,high load capacity,wear resistance,oil resistance
- ✔ Environmental protection,quiet,effectively protect the floor
- ✔ Painted,anti-rust and anti-corrosion
- ⚠ High temperature and humidity may shortened service life






Rolling resistance	■ ■ ■ ■ □	Very good
Wear resistance	■ ■ ■ ■ ■	Excellent
Operating noise	■ ■ ■ ■ □	Very good
Floor surface preservation	■ ■ ■ ■ □	Very good

Bracket Features


- ✔ Steel plate pressed and fully welded,firm and strong
- ✔ Thickened top plate,resistant to compress which is hard to deform
- ✔ Plane bearing,high load capacity,impact resistance and flexible steering
- ✔ Blue galvanized,ROHS/REACH passed,salt spray test over 72 hours
- ✔ ON/OFF pedals,stable braking effect,easy to operate
- ✔ Brake part is replaceable,convenient to maintain

Parameter (mm)							
Wheel Size	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
4"	380 kg	100	45	155	34	84	148
5"	480 kg	125	48	176	38	101	151
6"	580 kg	150	50	201	44	119	154
8"	720 kg	200	50	252	54	154	173



[English]

Mounting Drawing



Product ID	Product Images	Wheel Size	Plate swivel	Plate fixed	Plate swivel brake
4"		36A01-0128	36A03-0128	36A02-0128	
5"		36A04-0129	36A06-0129	36A05-0129	
6"		36A07-0130	36A09-0130	36A08-0130	
8"		36A10-0131	36A12-0131	36A11-0131	

Product Details

ON/OFF brake is easy to operate. Brake components can be replaced with screw connecting.



Planar bearings can match high loading capacity, impact resistance and flexible in rotation.



Double-sides welding, firm and strong. The top plate is thickened by 7.5mm.

