

Wheel Features

Tread Material:	TPR	Core Material:	High Strength PP
Bearing:	Single Ball Bearing	Tread Hardness:	80A±3
Temperature:	-15°C~60°C	Running Speed:	3.2km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ Precision ball bearing, flexible rotation
- ✔ Advanced thermo-plastic rubber, silent running, elastic to protect floor
- ✔ Environmental protection, quiet, effectively protect the floor
- ⚠ Economical material with common load capacity





Rolling resistance	■ ■ ■ □ □	Good
Wear resistance	■ ■ ■ □ □	Good
Operating noise	■ ■ ■ ■ ■	Excellent
Floor surface preservation	■ ■ ■ ■ ■	Excellent

Bracket Features




- ✔ Easy to operate, convenient to release the brake
- ✔ Spindle equipped with precision bearing, quiet and flexible
- ✔ Nylon-injection core, lightweight and tough
- ✔ Galvanized, salt spray test over 48 hours
- ✔ This product has passed TUV certification. Utility model patent owned, protected by intellectual property law.

Parameter (mm)							
Wheel Size	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
4"	50 kg	100	18	125.5	30	80	108
5"	80 kg	125	18	155.5	37.5	100	135
Wheel Size	Total height	Total height					
4"	123	115					
5"	155	145					



[English]

Mounting Drawing



Product ID						
Wheel Size	Plate swivel	Plate fixed	Threaded stem	Threaded stem brake	Stem of swivel	Stem of brake
4"	80T03-1747	80T04-1747	80T21-1747	80T22-1747	80T15-1747	80T16-1747
5"	80T05-1748	80T06-1748	80T23-1748	80T24-1748	80T17-1748	80T18-1748

Product Details



Split brake is easy to operate.

Nylon bracket is Integrated injection molding, front and back body are surrounded with high strength.



Double TPR wheel is silent, wear-resistant and water-resistant.

